# **Block Dimensions**

### Classic 8

## General Information

Absorption...Meets or exceeds ASTM C90-75 standards

Compressive strength...3000 PSI Approximate minimum (unless otherwise specified)

Composition . . . High strength, high density, "0" slump concrete

## Unit Information

Beveled Classic Unit:

8"H X 18"W X 12"D, 78 Lbs. Approx. . . . . 1.00 Sq. Ft. Face

Straight Classic Unit:

8"H X 18"W X 12"D, 78 Lbs. Approx. . . . . 1.00 Sq. Ft. Face

Colonial 18 Unit:

8"H X 18"W X 12"D, 78 Lbs. Approx. . . . . 1.00 Sq. Ft. Face

Colonial 6/12 Unit:


8"H X 6"/12"W X 12"D, 78 Lbs. Approx. . . . . 1.00 Sq. Ft. Face


Universal Cap

4"H X 18"W Front and 4"H X 14"W Back, 54 Lbs, Approx. 0.50 Sq. Ft. Front, 0.39 Sq. Ft.Back
Average running length is 16" (see installation manual)


#### Face Options


Face Patterns . . . . Beveled Split Face Straight Split Face Colonial Split Face







Universal Cap - Back














Impermeable Compacted Fill






This drawing is furnished for preliminary design purposes only, and should not be used for final design drawings or construction drawings without the certification of a professional engineer registered in the state in which the wall will be constructed

Date.











Geogrid	Drawing Pad		4" Crushed Project Location:		Project Name:
	Block Dimensions	Drawing Description:	YY	ocation: XX	
Project Number: WWWPRO	Date: MM/DD/YYYY	Sheet i	Drawn By:		Prepared for:
		# or \$	0		J D
		\$	Checked By:	Ō à	n n